

Configurator HBA

SERIES								
HBA	HBA - HIMAX							
	Code	LAMP TYPE						
	Simple module							
	.L144	14.000 lm 4000 K (IP44) // 12.700lm 4000K (IP65)						
	.L164	16.000 lm 4000 K (IP44) // 14.400lm 4000K (IP65)						
	.L214	21.800 lm 4000 K (IP44) // 19.600lm 4000K (IP65)						
	.L254 (1)	25.000 lm 4000 K (IP44) // 22.500lm 4000K (IP65)						
	Double module							
	.L324 (1)	32.000 lm 4000 K (IP44) // 28.800lm 4000K (IP65)						
	.L434 (1)	43.000 lm 4000 K (IP44) // 39.200lm 4000K (IP65)						
	.L504 (1)	50.000 lm 4000 K (IP44) // 45.000lm 4000K (IP65)						
	Code	OPTICAL DISTRIBUTION						
	.E1	Extensive optical distribution						
	.R1	Intensive optical distribution						
	Code	COLOUR						
	.910M	White RAL 9010 Matte						
	Code	CONTROL GEAR						
	.LRD	LED Dali Dimmable						
	Code	WATERTIGHTNESS						
	.IP44	Luminaire is watertight to IP44						
	.IP65 (2)	Luminaire is watertight to IP65						
	Code	EMERGENCY (OPTIONAL)						
	.S-EMERG	No emergency						
	.EM3	3 hours' operation						
	Code	FIXATION						
	.G4	Suspension system by two points up to 40cm from the roof.						
	.3S	Suspension system by two points up to 3m from the roof.						
	.SM	Surface fixation						
	.SF	Without fixation						
	Code	CABLES						
	.S-CAB	Without cables						
	.FL15	5 cables of length 1m						
	.FL35	5 cables of length 3m						
	.FL16	6 cables of length 1m						
	.FL36	6 cables of length 3m						
HBA	.L114	.E1	.910M	.LRD	.IP44	.S-EMERG	.4G	.S-CAB

(1) Light source only available with optical distribution E1.

NOTE: 5 Cables available for non-emergency versions. 6 cables available for EM3 emergency versions.